

Crosby® Grade 100 Foundry Hooks

Fatigue Rated

"QT"
QUENCHED & TEMPERED

QUIC-CHECK
Q


Crosby 8/10™

A-1359



- Forged Alloy Steel - Quenched and Tempered.
- Individually Proof Tested to 2-1/2 times the Working Load Limit with certification.
- Each hook has a Product Identification Code (PIC) for material traceability, along with the size and the name Crosby & U.S.A. in raised letters.
- Suitable for use with Grade 100 chain in overhead lifting applications as long as hook is Proof Tested as part of the chain sling assembly or as an individual component. Per ANSI B30.9-1.
- Fatigue rated at 1-1/2 times the Working Load Limit at 20,000 cycles.
- "Look for the Platinum Color - Crosby Grade 100 Alloy Products."

A-1359 Clevis Foundry Hook



Chain Size		Working Load Limit (t)*	A-1359 Stock No.	Weight Each (kg)	Dimensions (mm)							
(in.)	(mm)				A	C	D	F	G	K	N	AA
1/4	7	2.0	1049907	0.95	159	112	122	63.5	28.7	22.4	39.9	88.9
5/16	8	2.6	1049911	0.95	159	111	122	63.5	28.7	22.4	39.9	88.9
3/8	10	4.0	1049916	1.95	197	141	148	76.2	35.1	33.0	47.8	102
1/2	13	6.8	1049925	3.60	238	169	179	88.9	41.4	38.1	57.2	114
5/8	16	10.3	1049934	6.44	286	195	208	102	55.6	44.5	64.3	127
3/4	18-20	16.0	1049943	11.2	367	249	245	127	61.0	55.9	86.1	152
7/8	22-23	20.0	1049952	19.9	413	280	280	140	78.0	69.1	95.0	165

* Ultimate Load is 4 times the Working Load Limit.